

Special Matting Frames



Usage

It is recommended that for all Gegus E-M-S matting systems frames are required unless there is a pre-existing frame. They provide an accurate base within the mat well upon which to seat a mat. A correctly sized frame holds the mat rigidly in place and allows ease of access to the mat well for cleaning purposes or removal of the mat. Top Clean Trend 10 mm and 17 mm can be used surface mounted with the Special Ramped Edge Frame in applications where a fitting well is impractical or undesirable (please also see page 32).

Specification

Material	Angle profiles made of aluminium, brass and stainless steel
Height	For use with Top Clean mats 10, 17, 22, 27 and 42 mm
Application	See table below
Colours	On request powder coated aluminium profile can be supplied to any RAL colour (for an extra charge)
Special Shapes	Gaps/curves and diagonales can be manufactured after drawing or template for an extra charge (also see page 34).

Special Matting Frames (on mitre sawed and with special connectors screwed together)



Aluminium			Brass			Stainless Steel			Height of the Mat
Height	Width	Thickness	Height	Width	Thickness	Height	Width	Thickness	
15	20	3 mm	15	20	3 mm	15	15	2 mm	10 / 12 mm
20	20	3 mm	20	20	3 mm	20	20	3 mm	17 mm
25	25	3 mm	25	25	3 mm	25	25	3 mm	22 mm
30	30	3 mm	30	30	3 mm	30	30	3 mm	27 mm
45	30	3 mm							42 mm